



SENOR TECH CO., LTD.

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.

Tel: +886-2-26950405 Fax: +886-2-26952745

http://www.senortech.com E-mail:sales@senortech.com



### GTP-250 Thermal Printer

2009/7/30

Item		Details
Printer	Printing Method	Thermal Line Printing
	Dot Density	180 (7dots/mm)
	Printing Width	72mm
	Characters per line (Default)	42 (Font A) / 56 (Font B)
	Printing Speed *1)	47 lines/sec, 200 mm/sec
	Receive Buffer Size	4KBytes
	SMPS Input Voltage	100~240 VAC
	Frequency	50/60 Hz
	SMPS Output Voltage	24 VDC
	Temperature	0 ~ 45 °C (Operating) -10 ~ 50 °C (Storage)
	Humidity	30 ~ 80 % RH (Operating) 10 ~ 90 % RH (Storage) ; Except for paper
	Auto Cutter	1,800,000 Cuts
	Mechanism MCBF *2)	70,000,000 Lines
Paper	Paper Type	Paper Roll
	Roll Width	80mm
	Roll Diameter	Max 83mm
	Paper Thickness	0.062~0.075mm
	Paper Tube	Inner: Ø12mm (0.47") Outer: Ø18mm (0.71")

※NOTE: The product information and specifications are subject to change without notice.