



GTP-180 Thermal Printer

Senor's cost-effective & friendly GTP180, designed for retailers, is fast, high reliability. It features printing up to 250mm/second.

The GTP180 printer is compatible with electronic instrument, such as ECR, POS, cash register, receipt bill, computer peripheral equipment etc.

- Triple I/F : USB / Ethernet & Serial.
- 250mm/s high speed printing, easy to maintain, improve work efficiency.
- Low noise, high speed image & characters printing.
- Easy paper loading, with auto cutter, partial/full cut optional.
- Flexible installation on countertop or wall using optional bracket.
- Support paper out alarm and print prompt, improved spill resistant cover for added durability.

Printing Property	Dimension ($L \times W \times H$)	195×146×147mm
	Printing Method	Thermal Line
	Resolution	203X203dpi (8dots/mm)
	Paper Width	79.5±0.5mm
	Printing Width	72mm
		ASCII Font A : 12X24
	Printing Character	ASCII Font A : 9X24
		Character 12X24
	Printer Density	512dot/line or 576dot/line
	Printing Speed	250mm/s
	NV bitmap Flash	64kb
	Receipt Buffer	8kb
Power Adaptor	Input Voltage	AC 100~240V
	Rate	50/60Hz
	Output Voltage	DC 24V ' 2.5A
Environment	Operating Temperature	0~45°C
	Storage Temperature	-10~50°C
	Operating Humidity	10-80%
	Storage Humidity	10-90%
Life Span	Thermal Mechanism	15,000,000 lines
		10X105(~100km)
	Auto-cutter	10X105(~100km) 1,000,000 cuts 60,000,000 line ty & SDK for Wireless LAN/OPOS
	MCBF	60,000,000 line
Driver	Windows Driver / Linux / Android Utility & SDK for Wireless LAN/OPOS	

Note : Printer speed changes as the as the combination of the data transmission speed and control command varies.



No. 165, Kangning Street, Xizhi District, New Taipei City 22150, Taiwan

Tel: +886-2-2695-2780 Fax: +886-2-2695-2745 E-mail: sales@senortech.com http://www.senortech.com







